

## **Final Electric**

- Verify GFCI & AFCI protection where needed
  - o GFCI protection for <u>all 125-volt through 250-volt receptacles</u> in the following locations 210.8(A):
    - Basement
    - Bathroom
    - Laundry area
    - Garage
    - Kitchen
    - Within 6' of inside edge of sink (receptacles & fixed or stationary plug-and-cord-connected appliances)
    - Within 6' of outside edge of tub, shower
    - Exterior
    - Crawlspace
    - Areas with sinks and permanent provisions for food preparation, beverage preparation, or cooking
    - Indoor damp and wet locations
    - Service receptacle within 25' of HVAC equipment (interior & exterior) 210.8(E), 210.63

## o GFCI protection for the following appliances 210.8(A):

- Sump pumps
- Dishwashers
- Electric ranges
- Wall-mounted ovens
- Counter-mounted cooking units
- Clothes dryers
- Microwave ovens

\*GFCI receptacles must be "Readily Accessible"

- GFCI for crawl space lighting outlets 210.8(C)
- GFCI for cables in electrically heated floors in bathroom, kitchens, and in hydromassage bathtub locations 424.44(E)
- GFCI for fountains: Submersible lights, pumps, and other submersible equipment (unless not required for low- voltage); sign within fountain; receptacles within 20' of fountain edge 680.51
- o **AFCI 210.12**:
  - All 120V 15- and 20-amp circuits require AFCI protection except bathroom, garage, attic, unfinished basement, and exterior (fire alarm system is excluded)

\*This includes existing circuits that are modified (outlets or devices added) or extended more than 6' 210.12(D)



- Verify clear working space for panels and HVAC disconnects 110.26, 440.14
- All breakers must be clearly labeled 408.4(A)
- Verify whole-house surge protection 230.67(A)
- Seal around exterior luminaires 410.10
- Intersystem bonding terminal needed 250.94
- Lock-out device (padlock attachment) needed on breaker(s) for permanently connected appliances (if breaker is not within sight from appliance) 422.31
- Label outside cover of exterior "Emergency Disconnect, Service Disconnect" (cannot be handwritten) 230.85(E)
- Ensure Service Disconnect is labeled 230.70(B)